

GyroShift 3" Flush Mount Cylinder

25W LED Surface Mount
Round


Catalog #:

Type:

Project:

Date:

Notes:



STANDARD FINISHES

	ABL (Aegean Blue)		PNC (Painted Natural Copper)
	BB (Burnished Bronze)		RD (Red)
	BK (Gloss Black)		SGR (Sage Green)
	BLU (Blue)		SND (Sand)
	DVG (Dove Gray)		SS (Satin Silver)
	FLG (Flannel Gray)		TBZ (Textured Bronze)
	GA (Galvanized)		TGP (Textured Graphite)
	GWT (Gloss White)		TNG (Tangerine)
	LG (Lime Green)		TTL (Tahitian Teal)
	MB (Matte Black)		WT (Semi Gloss White)
	MBL (Midnight Blue)		YEL (Yellow)
	PNA (Painted Natural Aluminum)		

Electrical Data

CCT	CRI	Wattage	Delivered Lumens	Efficacy
2700K	90 CRI	25W	1550 lm	62 lpw
3000K	90 CRI	25W	1640 lm	65 lpw
3500K	90 CRI	25W	1725 lm	69 lpw
4000K	90 CRI	25W	1795 lm	72 lpw
Warm Dim	-	10W	608 lm	61 lpw

Lumens will vary depending on CCT, optic & lens option

Specifications

Field Replaceable LED Light Engine

- 25W LED with 2 SDCM binning
- 2700K, 3000K, 3500K and 4000K at 90 CRI
- 10°, 30° and 50° optics included
- 45° adjustability with 360° aiming

Field Replaceable Dimming Driver

- Multiple dimming drivers available
- Power factor > 0.9, 50/60Hz

Mounting

5" x 2-1/4" canopy included with standard universal dim driver. (7-1/8" x 2-1/4" round canopy included with Lutron and eldoLED drivers)

Finishes

Available in many colors with optional coastal coating to protect finish in coastal environments

Listing / Warranty

- Five (5) year limited warranty
- UL listed to US and Canadian standards for damp location



Order Matrix

GyroShift 3" Flush Mount Cylinder (Example: LF3-SFT-10S2710ABL-NLNL-0)

Series	Wattage	Driver	CCT / CRI	Optic	Finishes	Coastal Coating Option	Media 1	Media 2	Rev	Canopy
LF3-SFT (Round)	-10 (10W)	S² (ERP, Universal Dim, Triac/ELV/0-10V 10% 120-277V)	27 (2700K/90 CRI)	10	ABL	(blank) (No coating)	-NL (No Lens)	NL	-0	(blank) (standard canopy)
	-15 (15W)		30 (3000K/90 CRI)	30	BB	-C (Coating)	-CL (Clear Lens)	CL		-CC1³ (Conduit 3-1/4" canopy)
	-20 (20W)		35 (3500K/90 CRI)	50	BK		-FR (Frosted Lens)	FR		-CC2 (Conduit 3-7/8" canopy)
	-25 (25W)	L1¹ (Lutron Hi-lume® 2-Wire 1% 120V)	40 (4000K/90 CRI)		BLU		-MP (Solite Lens)	MP		
			WD* (1850-3000K)		DVG		-LS (Linear Spread)	LS		
		L3¹ (Lutron Hi-lume® Fade-to-Black 1% 120-277V)		FLG		-HEX* (Hex Louver)				
		EL1¹ (eldoLED DALI 1% 120-277V)		GA		-WW* (Wall Wash)				
		EL2¹ (eldoLED 0-10V 1% 120-277V)		GWT						
		DMX¹ (DMX 1% 120-277V)		LG						
				MB						
				MBL						
				PNA						
				PNC						
				RD						
				SGR						
				SND						
				SS						
				TBZ						
				TGP						
				TNG						
				TTL						
				WT						
				YEL						

1. Includes larger canopy
2. Forward and reverse dimming at 120V only
3. CC1 and CC2 only for S driver option

Media

S3-LENS-CL-0 (Clear Lens)	S3-LENS-LS-0 (Linear Spread)	*Note: Can only fit 1 media if HEX or WW is selected
S3-LENS-FR-0 (Frosted Lens)	S3-LENS-HEX-0* (Hex Louver)	
S3-LENS-MP-0 (Solite Lens)	S3-LENS-WW-0* (Wall Wash)	

Emergency

EM-1000 (25W LED Remote Inverter)
EM-1002 (10W LED Remote Emergency Driver)

Spec-00252 Revised 10/08/2021

Patent: www.csllighting.com/patents

14508 Nelson Ave. City of Industry, CA 91744 • tel: 626.336.4511 • fax: 626.330.4266 • www.csllighting.com
©2021 Creative Systems Lighting, A Division of Troy-CSL Lighting, Inc. All rights reserved. Subject to change without notice.

