





SS4021-30-BLU



SS4021-27-DVG-BC



STANDARD FINISHES

ABL (Aegean Blue)	PNC (Painted Natural Copper)
BB (Burnished Bronze)	RD (Red)
BK (Gloss Black)	SGR (Sage Green)
BLU (Blue)	SND (Sand)
DVG (Dove Gray)	SS (Satin Silver)
FLG (Flannel Gray)	TBZ (Textured Bronze)
GA (Galvanized)	TGP (Textured Graphite)
GWT (Gloss White)	TNG (Tangerine)
LG (Lime Green)	TTL (Tahitian Teal)
MB (Matte Black)	WT (Semi Gloss White)
MBL (Midnight Blue)	YEL (Yellow)
PNA (Painted Natural Aluminum)	

Electrical Data

CCT	CRI	Wattage	Delivered Lumens	Efficacy
2700K	90 CRI	25W	1579lm	63lpw
3000K	90 CRI	25W	1691lm	68lpw
3500K	90 CRI	25W	1817lm	73lpw
4000K	80 CRI	25W	2403lm	96lpw

Multiplier for Delivered Lumens

Wattage	10	15	20	25
Multiplier	0.45	0.69	0.83	1

Specifications

Description

A decorative, directional light that combines stylish design with a dimmable, energy efficient light source.

Mounting

Surface mounted directly over junction box

Suspension

- Cord mount provided with 10' of cord and (2) two black wet location grommets
- Stem mount provided with hang-straight canopy and 4' stem: (1) 6", (2) 12" & (1) 18" (includes couplers); Contact factory for custom stem.

Field Replaceable LED Light Engine

- 25W LED with 2 SDCM binning
- 2700K, 3000K and 3500K at 90 CRI / 4000K at 80 CRI
- 10°, 30°, 50° and 80° optics
- 50,000 hours at 70% lumen maintenance (L70)

Finishes

Available in 22 standard finishes with optional coastal coating to protect finish in coastal environments.

Field Replaceable Dimming Driver

- Universal dimming (Triac, ELV and 0-10V)
- Remote Lutron Hi-lume 2-Wire available
- Power factor > 0.9, 50/60Hz

Housing

Machined aluminum housing with solite glass lens

Listing / Warranty

- Five (5) year limited warranty
- UL listed to US and Canadian standards for wet locations



Order Matrix

Entity (Example: SS4021-10-35-10-DVG-2-BC)

Series	Wattage	CCT / CRI	Optic	Finish	Coastal Coating Option	Rev	Driver	Suspension	Canopy
SS4021	-10	-27 (2700K / 90 CRI)	-10	-ABL (Aegean Blue)	(blank) (No coating)	-2	-S ¹ (ERP, Universal Dim, Triac/ELV/0-10V 1% 120-277V) -LR1 (Remote Lutron Hi-lume [®] 2-Wire 1% 120V)	(blank) Flush	(blank) (standard canopy)
	-15	-30 (3000K / 90 CRI)	-30	-BB (Burnished Bronze)	-C (Coating)			-WC 10' White Cord	-CC1 ³ (Conduit 3-1/4" canopy)
	-20	-35 (3500K / 90 CRI)	-50	-BK (Gloss Black)				-BC 10' Black Cord	
	-25	-40 (4000K / 80 CRI)	-80	-BLU (Blue)				-ST* Stem	-CC2 ³ (Conduit 3-7/8" canopy)
				-DVG (Dove Gray)				-LV 10' Low Voltage Aircraft Cable	
				-FLG (Flannel Gray)					*Stem kit includes: 6" - 1pc 12" - 2pcs 18" - 1pcs Couplers - 5pcs
				-GA (Galvanized)					
				-GWT (Gloss White)					
				-LG (Lime Green)					
				-MBL (Midnight Blue)					
			-MB (Matte Black)						
			-PNA (Painted Natural Aluminum)						
			-PNC (Painted Natural Copper)						
			-RD (Red)						
			-SGR (Sage Green)						
			-SND (Sand)						
			-SS (Satin Silver)						
			-TBZ (Textured Bronze)						
			-TGP (Textured Graphite)						
			-TNG (Tangerine)						
			-TTL (Tahitian Teal)						
			-WT (Semi Gloss White)						
			-YEL (Yellow)						

1. Forward and reverse dimming at 120V only

3. CC1 and CC2 only for S driver option